

# Power Splitter



**340-3800MHz**

- ◆ Wide-band design, cover 340-3800MHz
- ◆ Low PIM
- ◆ Compact size and light weight
- ◆ Easy to be installed
- ◆ Suitable for indoor and outdoor applications
- ◆ Square tube



## Technical Data

Electrical Specifications		Orbis code		Orbis code		Orbis code	
Type No.	PIM3 (@2x43 dBm Carrier) (dBc)	≤-150	95020133	95030133	95040133		
		≤-155	95020135	95030135	95040135		
		≤-160	95020137 3008483	95030137 3008484	95040137 3008485		
Frequency Range (MHz)		340-3800					
For connecting...antennas		2 Way	3 Way	4 Way			
Distribution Loss(dB)		3.0	4.8	6.0			
Insertion Loss (dB)		≤0.3	≤0.6	≤0.6			
Return Loss (dB)		≥19@340-2700&≥18@3400-3800					
Input Power (W)		≤300					
Peak Power (W)		≤1500					
Impedance (Ω)		50					
Mechanical Specifications							
Dimensions,HxWxD(excluding connectors and mounting bracket)(mm)		249x25x25	272.5x25x25	294.9x25x25			
Weight (including connectors and mounting bracket) (kg)		0.52	0.58	0.71			
Packing Size(mm)		290x85x50(30Pcs/box)	335x85x50(30Pcs/box)	355x85x65(30Pcs/box)			
Connector Type		4.3-10 Female(Twisthead)					
Color		Light Gray(Customizable)					
Mounting		Wall Mounted					

## Environmental Specifications

Operational Temperature (°C)	-25 to +65
Operational Humidity (%)	≤95
Ingress Protection Class	IP65(Indoor and Outdoor)

## Accessories(order separately)

Type No.	Description
30505.0043051	Bracket
50501.0330100	Screw

