

- ◆ Very Low PIM
- ◆ 100W average power
- ◆ Low VSWR
- ◆ Convenient Size
- ◆ For indoor/outdoor applications
- ◆ IP67 and RoHS compliant
- ◆ Multiple Connector Options
- ◆ SMA, N, 7-16 & 4.3-10



100W TK-27FD

Microlab TK-27 series of 100W Cable Loads are intended for wireless applications, when extremely low PIM, Passive Intermodulation, is required. A typical application is in terminating the unused port of a Hybrid Coupler used to combine different wireless signals. This is also offered as a discrete product in the CT series of low PIM hybrid combiners.


For IEC 60950 compliance (surface temperature no greater than 90°C) at full power at 55°C ambient, air flow over the fins is required.

Frequency: 350 - 2700 MHz
Power Rating[†]: 100W avg., 5 kW peak
PIM: -161 dBc, tested with 2 20W tones at 25°C
Environment: -35 to +55°C ambient, IP67
Surface Temp: +110°C max.*
Impedance: 50Ω nom.
Connector Finish: Triplate
Weight, nom: 5.55 lb., 2.50 Kg
Enclosure: Black epoxy paint, mounting bracket supplied

* Measured on heat sink fin, at full power into a unit that is mounted in a 2 RU and 19" box, all enclosed and without cooling, at 25°C external ambient temperature

[†] Derate Avg Power by -1.2%/°C above 55°C ambient

| Model Number and Connector | | | | | | | VSWR | | | |
|----------------------------|-------------|-----------|----------------|--------------|------------------|----------------|---------------------|---------------------|------------------------|------------------------|
| †SMA Female | N Female | N Male | 7/16 Female | 7/16 Male | 4.3-10 Female | 4.3-10 Male | 350-698 MHz typ. | 350-698 MHz max. | 698 - 2700 MHz typ. | 698 - 2700 MHz max. |
| TK-27FF | TK-27FN | TK-27MN | TK-27FD* | TK-27MD* | TK-27FE | TK-27ME | 1.20:1 | 1.25:1 | 1.10:1 | 1.15:1 |
| †SMA ver. made to order | | | | | | | *VSWR: 1.20:1 max | | | |



Note: Specifications are subject to change without prior notification.

06JUL2018

TK-27MN Outline
